



Konformitätserklärung

im Sinne der Richtlinie: 2014/35/EU Niederspannungsrichtlinie,
(Richtlinie 2014/35/EU des Europäischen Parlaments und des Rates vom 26.02.2014 zur Angleichung der
Rechtsvorschriften der Mitgliedstaaten betreffend elektrische Betriebsmittel zur
Verwendung innerhalb bestimmter Spannungsgrenzen)

im Sinne der Richtlinie: 2014/30/EU Elektromagnetische Verträglichkeit
(Richtlinie 2014/30/EU des Europäischen Parlaments und des Rates vom 26.02.2014 zur Angleichung der
Rechtsvorschriften der Mitgliedstaaten über die elektromagnetische Verträglichkeit)

Der Hersteller, **JB-Lighting Lichtenlagentechnik GmbH**
Sallersteigweg 15
89134 Blaustein-Wipplingen

erklärt, dass das Produkt: **Varyscan P18**

den wesentlichen Schutzanforderungen der Richtlinien entspricht. Es wurden folgende Normen zur Konformitätsbewertung herangezogen:

Aussendung - Anforderungen gemäß EN 55022:2010

Leitungsgeführte Störaussendung
EN 55022:2010
Abstrahlungen
EN 55022:2010
Oberschwingungsströme
EN 61000-3-2:2015
Flicker
EN 61000-3-3:2013

Einrichtungen der Informationstechnik, Funkstöreigenschaften - Grenzwerte und Messverfahren - Grenzwertklasse A

Einrichtungen der Informationstechnik, Funkstöreigenschaften -
Grenzwerte und Messverfahren - Grenzwertklasse A
Einrichtungen der Informationstechnik, Funkstöreigenschaften -
Grenzwerte und Messverfahren - Grenzwertklasse A
Elektromagnetische Verträglichkeit
Teil 3-2: Grenzwerte, Prüfung von Oberschwingungsströmen
(für Geräte mit einem Eingangsstrom < 16A pro Phase)
Elektromagnetische Verträglichkeit (EMV)
Teil 3-3: Grenzwerte, Begrenzung von Spannungsänderungen,
Spannungsschwankungen und Flicker in Niederspannungsnetzen
(für Geräte mit einem Eingangsstrom < 16A pro Phase)

Störfestigkeit - Anforderungen gemäß EN 61000-6-2:2005

EN 61000-4-2:2009
EN 61000-4-3:2006 +A1:2008 +A2:2010
EN 61000-4-4:2012
EN 61000-4-5:2006
EN 61000-4-6:2014
EN 61000-4-8:2010
EN 61000-4-11:2004

Elektromagnetische Verträglichkeit (EMV) - Teil 6-2: Fachgrundnorm – Störfestigkeit Industriebereich

Teil 4-2: Störfestigkeit gegen Entladung statischer Elektrizität
Teil 4-3: Störfestigkeit gegen hochfrequente elektromagnetische Felder
Teil 4-4: Störfestigkeit gegen schnelle transiente elektrische
Störgrößen (Burst)
Teil 4-5: Störspannungen gegen Stoßspannungen (Surge)
Teil 4-6: Störfestigkeit gegen leitungsgeführte Störgrößen,
induziert durch HF
Teil 4-8: Störfestigkeit gegen Magnetfelder mit energietechnischen
Frequenzen
Teil 4-11: Störfestigkeit gegen Spannungseinbrüche, Kurzzeit-
unterbrechungen und Spannungsschwankungen

Blaustein, den 01.02.2018



Jürgen Braungardt
Geschäftsführer



Declaration of Conformity

in terms of directive 2014/35/EU - low voltage directive
(Directive 2014/35/EU of the council from 26. February 2014 on the harmonisation of the laws of Member States relating to electrical equipment designed for use within certain voltage limits)

in terms of directive 2014/30/EU - electromagnetic compatibility
(Directive 2014/30/EU of the council from 26. February 2014 on the approximation of the laws of the Member States relating to electromagnetic compatibility)

The Manufacturer **JB-lighting Lichtenlagentechnik GmbH**
Sallersteigweg 15
89134 Blaustein-Wipplingen

declare that the product **Varyscan P18**

is in agreement with the safety requirements of this directives. Following standards are contained in the evaluation of the declaration of conformity:

Emission - requirements according to: EN 55022:2010

Conducted emissions
EN 55022:2010
Radiated emissions
EN 55022:2010
Harmonic current emissions
EN 61000-3-2:2015

Flicker
EN 61000-3-3

Information technology equipment - Radio disturbance characteristics - Limits and methods of measurements - Class A

Information technology equipment - Radio disturbance characteristics - Limits and methods of measurements - Class A
Information technology equipment - Radio disturbance characteristics - Limits and methods of measurements - Class A
Electromagnetic compatibility (EMC)
part 3-2: Limits - Limits for harmonic current emissions (equipment input current < 16A per phase)
Electromagnetic compatibility (EMC)
part 3-3: Limits - Limitation of voltage changes, voltage fluctuation and flicker in public low-voltage supply systems, for equipment with rated current < 16 A per phase and not subjected to conditional connection

Immunity - Requirements according to DIN EN 61000-6-2:2005

EN 61000-4-2:2009
EN 61000-4-3: 2006 + A1:2008 + A2:2010
EN 61000-4-4:2012
EN 61000-4-5:2006
EN 61000-4-6:2014
EN 61000-4-8:2010
EN 61000-4-11:2004

Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity for industrial environments

Part 4-2: Testing and measurements techniques
Electrostatic discharge immunity test
Part 4-3: Testing and measurements techniques
Radiated, radio-frequency, electromagnetic field immunity test
Part 4-4: Testing and measurements techniques
Electrical fast transient/burst immunity test
Part 4-5: Testing and measurements techniques
Surge immunity test
Part 4-6: Testing and measurements techniques
Immunity to conducted disturbances, induced by radio-frequency fields
Part 4-8: Testing and measurements techniques
Power frequency magnetic field immunity test
Part 4-11: Testing and measurements techniques
Voltage dips, short interruptions and voltage variations immunity tests

Blaustein, 01.02.2018

Jürgen Brauhgardt
Managing Director