

P5 HP

Beleuchtungsstärke in Lux / Illuminance in lux

Beamwinkel/Beam angle: 2,4° (Zoom min.)

Distance (m)	2	4	6	8	10	12	14	16	18	20
Ø (m)	0,09	0,17	0,26	0,34	0,43	0,51	0,6	0,68	0,77	0,85
Boost (Lux)	477633	119408	53070	29852	19105	13268	9748	7463	5897	4776
Standard (Lux)	467909	116977	51990	29244	18716	12997	9549	7311	5777	4679
Silent (Lux)	427370	106843	47486	26711	17095	11871	8722	6678	5276	4274
Whisper (Lux)	371081	92770	41231	23193	14843	10308	7573	5798	4581	3711

Beamwinkel/Beam angle: 21,2°

Distance (m)	2	4	6	8	10	12	14	16	18	20
Ø (m)	0,75	1,5	2,25	3	3,75	4,49	5,24	5,99	6,74	7,49
Boost (Lux)	24900	6225	2767	1556	996	692	508	389	307	249
Standard (Lux)	24393	6098	2710	1525	976	678	498	381	301	244
Silent (Lux)	22280	5570	2476	1392	891	619	455	348	275	223
Whisper (Lux)	19345	4836	2149	1209	774	537	395	302	239	193

Beamwinkel/Beam angle: 50° (Zoom max.)

Distance (m)	2	4	6	8	10	12	14	16	18	20
Ø (m)	1,82	3,64	5,45	7,27	9,09	10,9	12,7	14,5	16,4	18,2
Boost (Lux)	5074	1268	564	317	203	141	104	79	63	51
Standard (Lux)	4970	1243	552	311	199	138	101	78	61	50
Silent (Lux)	4540	1135	504	284	182	126	93	71	56	45
Whisper (Lux)	3942	985	438	246	158	109	80	62	49	39

